



EXCELLENT HIGH QUALITY PTFE TAPE

12m x 0.1 x 12mm

Made out of 100% virgin PTFE

GENERAL DESCRIPTION:

For sealing metal and synthetic threaded connections. Suitable for gas, water, oxygen steam, fuels, solvents and acids.

- 100% PTFE
- Chemical Resistant
- Mould Resistant
- UV Resistant
- Removable
- Oxygen Grade
- Immediately loadable

TECHNICAL DATA

Colours:	White
Thickness:	0.1mm
Width and Length	12 mm x 12m 19mm x 30m
Working Temperature:	-40°C to 260°C
Tensile Strength:	15N/mm ²

**Pressure rating is relative to the torque and quality of the threads and the amount of tape used.*

NOTE

Except where indicated otherwise, the figures stated are test average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'.

PTFE APPLICATIONS

- Acids, concentrated (see precautions) or dilute
- Air, compressed
- Alcohols
- Aliphatic Solvents
- Ammonia, liquid
- Aromatic, solvents
- Caustics, concentrated (see precautions) or dilute
- Chlorinated solvents
- Cutting oils
- Diesel fuel oil
- Ethylene Glycol
- Fatty Acids
- Gasohol
- Gasoline
- Glycerine
- Heating Oils
- Hydraulic Fluids
- Hydraulic Acids
- Hydrogen gaseous or liquid.
- Inert gases, gases, gaseous or liquid.
- Jet Fuel
- Kerosene
- Ketones
- Liquid Petroleum gas
- Mineral Oils
- Nitrogen, gaseous or liquid
- Soap, liquid
- Steam
- Vegetable Oils
- Water

PRODUCT NUMBER	BAR CODE	CASE SIZE	CARTON WEIGHT	QUANTITY
5003012	38753314020	58 x 28 x 39cm	18.3kg	1000
5003030	38753312125	55 x 44 x 45cm	29.9kg	1000